

## ANSI (ASTM) CARBON & ALLOY STEEL PIPE DIMENSIONS [mm] AND WEIGHT [kg]

Nominal Bore		Outside Diameter	Wall Thickness	10	20	30	STD	40	60	XS	80	100	120	140	160	XXS
ins	mm	mm	/ Mass													
1/8"	6	10.3	mm				1.73	1.73		2.41	2.41					
			kg/m				0.37	0.37		0.47	0.47					
1/4"	8	13.7	mm				2.24	2.24		3.02	3.02					
			kg/m				0.63	0.63		0.80	0.80					
3/8"	10	17.1	mm				2.31	2.31		3.20	3.20					
			kg/m				0.84	0.84		1.10	1.10					
1/2"	15	21.3	mm				2.77	2.77		3.73	3.73				4.78	7.47
			kg/m				1.27	1.27		1.62	1.62					1.95
3/4"	20	26.7	mm				2.87	2.87		3.91	3.91				5.56	7.82
			kg/m				1.69	1.69		2.20	2.20					2.90
1"	25	33.4	mm				3.38	3.38		4.55	4.55				6.35	9.09
			kg/m				2.50	2.50		3.24	3.24					4.24
1 1/4"	32	42.2	mm				3.56	3.56		4.85	4.85				6.35	9.70
			kg/m				3.39	3.39		4.47	4.47					5.61
1 1/2"	40	48.3	mm				3.68	3.68		5.08	5.08				7.14	10.15
			kg/m				4.05	4.05		5.41	5.41					7.25
2"	50	60.3	mm				3.91	3.91		5.54	5.54				8.74	11.07
			kg/m				5.44	5.44		7.48	7.48					11.1
2 1/2"	65	73.0	mm				5.16	5.16		7.01	7.01				9.52	14.02
			kg/m				8.63	8.63		11.4	11.4					14.9
3"	80	88.9	mm				5.49	5.49		7.62	7.62				11.13	15.24
			kg/m				11.3	11.3		15.3	15.3					21.4
3 1/2"	90	101.6	mm				5.74	5.74		8.08	8.08					
			kg/m				13.6	13.6		18.6	18.6					
4"	100	114.3	mm				6.02	6.02		8.56	8.56		11.13		13.49	17.12
			kg/m				16.1	16.1		22.3	22.3		28.3		33.5	41.0
5"	125	141.3	mm				6.55	6.55		9.52	9.52		12.7		15.88	19.05
			kg/m				21.8	21.8		31.0	31.0		40.3		47.91	57.4
6"	150	168.3	mm				7.11	7.11		10.97	10.97		14.27		18.26	21.95
			kg/m				28.3	28.3		42.6	42.6		54.2		67.6	79.2
8"	200	219.1	mm		6.35	7.04	8.18	8.18	10.31	12.7	12.7	15.09	18.26	20.62	23.01	22.23
			kg/m		33.3	36.8	42.6	42.6	53.1	64.6	64.6	75.9	90.4	100.9	111.3	107.9
10"	250	273.0	mm		6.35	7.80	9.27	9.27	12.70	12.70	15.09	18.26	21.44	25.40	28.58	25.40
			kg/m		41.8	51.0	60.3	60.3	81.5	81.5	96.0	114.7	133.0	155.1	172.3	155.1
12"	300	323.8	mm		6.35	8.38	9.52	10.31	14.27	12.70	17.48	21.44	25.40	28.58	33.32	25.40
			kg/m		49.7	65.2	73.9	79.7	108.9	97.4	132.1	159.9	186.9	208.1	238.7	186.9
14"	350	355.6	mm	6.35	7.92	9.52	9.52	11.13	15.09	12.70	19.05	23.83	27.79	31.75	35.71	
			kg/m	54.7	67.9	81.3	81.3	94.6	126.7	107.4	158.1	195.0	224.7	253.6	281.7	
16"	400	406.4	mm	6.35	7.92	9.52	9.52	12.70	16.66	12.70	21.44	26.19	30.96	36.53	40.49	
			kg/m	62.7	77.8	93.3	93.3	123.3	160.1	123.3	203.5	245.6	286.7	333.2	365.4	
18"	450	457	mm	6.35	7.92	11.13	9.52	14.27	19.05	12.70	23.83	29.36	34.93	39.67	45.24	
			kg/m	70.6	87.7	122.4	105.2	155.8	205.8	139.2	254.6	309.6	363.6	408.3	459.4	
20"	500	508	mm	6.35	9.52	12.70	9.52	15.09	20.62	12.70	26.19	32.54	38.10	44.45	50.01	
			kg/m	78.6	117.2	155.1	117.2	183.4	247.8	155.1	311.2	381.6	441.5	508.2	564.9	
22"	550	559	mm	6.35	9.52	12.70	9.52	15.88	22.23	12.70	28.58	34.93	41.28	47.63	53.98	
			kg/m	86.6	129.1	171.1	129.1	213.0	294.3	171.1	373.9	451.5	527.1	600.7	672.3	
24"	600	610	mm	6.35	9.52	14.27	9.52	17.48	24.61	12.70	30.96	38.89	46.02	52.37	59.54	
			kg/m	94.5	141.1	209.7	141.1	255.4	355.3	187.1	442.1	547.7	640.1	720.2	808.3	
26"	650	660	mm		7.92	12.70	9.52			12.70						
			kg/m		127.4	202.7				202.7						

Global Supply Line keep large stocks of A234 WPB butt weld fittings up to 900NB from schedule 40 in STD weight up to XXS. We stock many hard-to-find sizes and schedules. GSL also stocks 900LB and schedule small diameter fittings in A105/A106 and WPB in weld end and NPT ends. In addition we keep large stocks of Geldbach A105 and LF2 flanges in 150 to 2500 class as well as API 6A 2,000 to 10,000 psi Neway Oil flanges in high yield carbon steel and alloy steel.

~ Fast Track Valve Manufacturer ~

*Australian Pipeline Valve provides this technical information to assist the valve community. Please share and refer us to any specifiers or purchasers of valves/actuators within your network.*

[Click here](#) for our full online stock list

© Copyright Australian Pipeline Valve 2024